Global Parts Order Processing Material Safety Data Sheet SELKIRK CHRYSLER (MB) LTD.

CHRYSLER

HAZARD COMMUNICATION SHEET

2013761 DRAFT MULTIPLE FORMULA PART/COMMTY CD: 05010884AA EFFECTIVE DATE: 08/23/10 SUPPLIER: 37637 MFGR: 03500 STANDARD: N/AV *** SECTION 01 - PRODUCT INFORMATION *** MFG BY: PART SALES & SERVICE CHRYSLER 26311 LAWRENCE AVE CENTERLINE MI 48015 EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888 DIST BY: PART SALES & SERVICE CHRYSLER 26311 LAWRENCE AVE CENTERLINE MI 48015 EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888 CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888 BRAND NAME: RTV1473 ACETOXY CURING SEALANT MFG ID : N/AV DESCRIPTION: SEALANT-RTV PRODUCT IDENTIFICATION NUMBER (PIN): N/AP *** SECTION 02 - INGREDIENTS *** HAZARDOUS INGREDIENTS: PERCENT CHRYSLER COMM NAME / CAS NO & CHEM NAME: BY WGT TWA STEL CEIL UNITS NOTATIONS N/AP N/AP N/AP N/AP LD50: N/AV N/A N/A IDLH: LC50: N/AV N/A N/A GENERIC DESC: MIXTURE(S) OF THE FOLLOWING: ALIPHATIC HYDROCARBON(S), SILICA CONTAINING COMPOUNDS AND POLYMER(S). FOR EXPLANATION OF "NOTATIONS", SEE THE HAZARD COMMUNICATION SHEET EXPLANATIONS PAGE. CONSULT LOCAL AUTHORITIES FOR ACCEPTABLE EXPOSURE LIMITS. *** SECTION 03 - PHYSICAL DATA *** BOILING POINT : N/AV C SOLUB IN WATER: N/AV VAPOR PRESSURE: N/AV EVAP. RATE: < 1.000 REF: BUTYLACETATE VAPOR DENSITY : N/AV SPECIFIC GRAVITY: 1.060 AT PH AT FULL STRENGTH: N/AV PH AT REC. DILUT: N/AV %VOLATILE BY VOL : 2.1 VOLATILE ORGANIC COMP: N/AV ODOR THRESHOLD: N/AV PPM FOR % POPULATION FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV APPEARANCE & ODOR: STATE: SOLID...., COLOR: BLACK.... AND ODOR: ACETIC ACID (VINEGAR).... *** SECTION 04 - FIRE AND EXPLOSION DATA ***

Global Parts Order Processing Material Safety Data Sheet SELKIRK CHRYSLER (MB) LTD. March 14, 2013 14:54

FLASH POINT: > 93 C N/AV IGN TEMP: N/AV LEL: N/AV UEL: N/AV SPECIAL FIRE & EXPLOSION HAZARDS:

NONE KNOWN.

EXTINGUISHING MEDIA:

WATER FOG, DRY CHEMICAL, CARBON DIOXIDE AND FOAM.

SPECIAL FIREFIGHTING PROCEDURES:

USE PROTECTIVE CLOTHING. USE SELF-CONTAINED BREATHING APPARATUS. EVACUATE PERSONNEL FROM AREA.

FLAMMABILITY CONDITIONS:

MAY IGNITE WHEN EXPOSED TO HEAT OR OPEN FLAME.

SENSITIVE TO MECHANICAL IMPACT?: NO SENSITIVE TO STATIC DISCHARGE?: NO HAZARDOUS COMBUSTION PRODUCTS:

CARBON MONOXIDE AND CARBON DIOXIDE, SILICON DIOXIDE AND FORMALDEHYDE.

FLAME PROJECTION: N/AV FLAMMABILITY: N/AV

*** CECTION OF DESCRIPTION DAMA

*** SECTION 05 - REACTIVITY DATA ***

STABILITY: STABLE CONDITIONS TO AVOID:

NONE KNOWN.

MATERIALS TO AVOID:

NONE KNOWN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION MAY PRODUCE THE FOLLOWING: CARBON MONOXIDE AND CARBON DIOXIDE, SILICON DIOXIDE AND FORMALDEHYDE.

*** SECTION 06 - TOXICOLOGICAL PROPERTIES ***

EFFECTS OF OVEREXPOSURE-ACUTE & CHRONIC:

<---INHALATION--->> NONE KNOWN. <---SKIN CONTACT--->> PRIMARY IRRITATION.

<<---EYE CONTACT--->> IRRITATION. <<---INGESTION--->> MAY BE HARMFUL IF
SWALLOWED. <<---SPECIAL TOXICITY--->> LIVER DAMAGE. AND MAY CAUSE
REPRODUCTIVE EFFECTS.

TOXICOLOGICALLY SYNERGISTIC PRODUCTS:

PRODUCT LD50: N/AV N/AV

N/AV N/AV N/AV N/AV

PRODUCT LC50: N/AV N/AV N/AV

*** SECTION 07 - PREVENTIVE MEASURES ***

RESPIRATORY PROTECTION:

IF THE ALLOWABLE LIMIT OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, USE THE FOLLOWING: FUME, DUST AND MIST RESPIRATOR OR AIRLINE RESPIRATOR.

VENTILATION TYPE:

GOOD GENERAL VENTILATION.

Giobal Parts Order Processing Material Safety Data Sheet SELKIRK CHRYSLER (MB) LTD.

March 14, 2013 14:54

PROTECTIVE GLOVES:

RECOMMENDED. COTTON GLOVES.

EYE PROTECTION:

RECOMMENDED. CHEMICAL GOGGLES.

OTHER PROTECTIVE EQUIP:

A SAFETY SHOWER MAY BE NEEDED FOR EMERGENCY SITUATIONS. AN EYE WASH MAY BE NEEDED FOR EMERGENCY SITUATIONS.

WEAR PROTECTIVE CLOTHING. SHOVEL INTO STORAGE CONTAINERS. MOP UP AREA. WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND FEDERAL DISPOSAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

STORE IN A COOL, DRY PLACE. USE WITH ADEQUATE VENTILATION. KEEP FROM HEAT, SPARK OR OPEN FLAMES. AVOID BREATHING DUST. AVOID SKIN CONTACT. AVOID EYE CONTACT. DO NOT SMOKE OR EAT WHEN HANDLING THIS SUBSTANCE; WASH THOROUGHLY AFTER USING.

OTHER PRECAUTIONARY MEASURES:

MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

*** SECTION 08 - FIRST AID MEASURES ***

.

EMERGENCY FIRST AID PROCEDURES:

<<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. ARTIFICIAL RESPIRATION IF
BREATHING HAS STOPPED. CARDIAC RESUSCITATION IF INDICATED. IF BREATHING IS
DIFFICULT, GIVE OXYGEN. IF CONDITION PERSISTS, CONSULT A PHYSICIAN.
<<---SKIN CONTACT--->> WASH WITH SOAP AND WATER. REMOVE CONTAMINATED
CLOTHING. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---EYE CONTACT--->>
RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING
BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. REMOVE CONTACT LENSES TO
ASSURE COMPLETE FLUSHING. IF CONDITION PERSISTS, CONSULT A PHYSICIAN.
<<---INGESTION--->> DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY. GIVE
SEVERAL GLASSES OF WATER OR MILK TO DRINK. NEVER GIVE ANYTHING BY MOUTH TO
AN UNCONSCIOUS PERSON. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT
LIQUID FROM SEEPING INTO THE WINDPIPE AND LUNGS.

*** SECTION 09 - PREPARED BY INFORMATION ***

DATA SHEET PREPARED BY:

INDUSTRIAL HYGIENE DEPARTMENT

CHRYSLER

PHONE: 248-512-8260

PREPARED BY: SK KECKAN

REVIEWED BY:

REVISED BY: