Global Parts Order Processing Material Safety Data Sheet SELKIRK CHRYSLER (MB) LTD.

C H R Y S L E R HAZARD COMMUNICATION SHEET

292126 DRAFT PART/COMMTY CD: 0VU01418 EFFECTIVE DATE: 03/16/11 SUPPLIER: 86056 MFGR: 03500 STANDARD: N/AV *** SECTION 01 - PRODUCT INFORMATION *** MFG BY: PART SALES & SERVICE CHRYSLER 26311 LAWRENCE AVE CENTERLINE MI 48015 EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888 DIST BY: PART SALES & SERVICE CHRYSLER 26311 LAWRENCE AVE CENTERLINE MI 48015 EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888 CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888 BRAND NAME: MOPAR GENERAL PURPOSE HI-TEMP WHEEL GREA MFG ID : N/AV DESCRIPTION: FLUID-TRANS/AXLE/BRAKES PRODUCT IDENTIFICATION NUMBER (PIN): N/AP *** SECTION 02 - INGREDIENTS *** HAZARDOUS INGREDIENTS: PERCENT CHRYSLER COMM NAME / CAS NO & CHEM NAME: BY WGT TWA STEL CEIL UNITS NOTATIONS ***EXISTING INGREDIENTS*** PARAFFINIC PROCESS OIL 60-100 5 10 N/AP MG/M3 064742-54-7A DISTILLATES (PETROLEUM LD50: 22.000GM/KG ORL MUS IDLH: N/AP LC50: N/AV N/AV N/A N/A DISTILLATES (PETROLEUM), HYDROTRE 60-100 5 10 N/AP MG/M3 064742-52-5A DISTILLATES (PETROLEUM LD50: 22.000GM/KG ORL MUS IDLH: N/AP LC50: N/AV N/AV N/A N/A RESIDUAL OILS (PETROLEUM), SOLVEN 60-100 5 10 N/AP MG/M3 064742-62-7A RESIDUAL OILS (PETROLE LD50: 22.000GM/KG ORL MUS IDLH: N/AP LC50: N/AV N/AV N/A N/A GENERIC DESC: MIXTURE(S) OF THE FOLLOWING: MINERAL OIL(S) AND ADDITIVES. FOR EXPLANATION OF "NOTATIONS", SEE THE HAZARD COMMUNICATION SHEET EXPLANATIONS PAGE. CONSULT LOCAL AUTHORITIES FOR ACCEPTABLE EXPOSURE LIMITS. *** SECTION 03 - PHYSICAL DATA *** BOILING POINT : N/AV C SOLUB IN WATER: NEGLIGIBLE (< 0.1%) VAPOR PRESSURE: < 1 MM HG AT 20 C EVAP. RATE: N/AV REF: N/AP VAPOR DENSITY : >10.000 AT 25 C SPECIFIC GRAVITY: 0.950 AT PH AT FULL STRENGTH: N/AP PH AT REC. DILUT: N/AP %VOLATILE BY VOL : N/AP VOLATILE ORGANIC COMP: N/AV ODOR THRESHOLD: N/AV PPM FOR % POPULATION

Page 1 of 4

Global Parts Order Processing Material Safety Data Sheet SELKIRK CHRYSLER (MB) LTD.

FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV APPEARANCE & ODOR: APPEARANCE: DARK COLOR: GREY STATE: PASTE, ODOR: PETROLEUM
*** SECTION 04 - FIRE AND EXPLOSION DATA ***
FLASH POINT: > 150 C N/AV IGN TEMP: N/AV LEL: N/AV UEL: N/AV SPECIAL FIRE & EXPLOSION HAZARDS: MAY REACT WITH OXIDIZERS. RELEASES TOXIC FUMES OR GASES WHEN HEATED TO DECOMPOSITION. EXTINGUISHING MEDIA: LARGE FIRE-ALCOHOL FOAM OR WATER FOG. SMALL FIRE-CARBON DIOXIDE OR DRY CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING. SPECIAL FIREFIGHTING PROCEDURES: USE WATER TO COOL FIRE EXPOSED CONTAINERS. TREAT AS A PETROLEUM OIL FIRE. DO NOT USE WATER IN STRAIGHT STREAMS. AVOID BREATHING VAPOR OR FUMES. USE PROTECTIVE CLOTHING. USE SELF-CONTAINED BREATHING APPARATUS. FLAMMABILITY CONDITIONS: MAY IGNITE WHEN EXPOSED TO HEAT OR OPEN FLAME. SENSITIVE TO MECHANICAL IMPACT?: NO SENSITIVE TO STATIC DISCHARGE?: N/AV HAZARDOUS COMBUSTION PRODUCTS: CARBON MONOXIDE AND CARBON DIOXIDE, SMOKE, VARIOUS HYDROCARBONS, OXIDES OF NITROGEN, OXIDES OF SULFUR, OXIDES OF PHOSPHORUS AND METAL OXIDE(S). FLAMME PROJECTION: N/AP FLAMMABILITY: N/AV
*** SECTION 05 - REACTIVITY DATA ***
STABILITY: STABLE CONDITIONS TO AVOID: HIGH TEMPERATURE, SPARKS OR OPEN FLAME. MATERIALS TO AVOID: STRONG OXIDIZING AGENTS, STRONG ACID. HAZARDOUS POLYMERIZATION: WILL NOT OCCUR POLYMERIZATION CONDITIONS TO AVOID: POLYMERIZATION WILL NOT OCCUR. HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE AND CARBON DIOXIDE, SMOKE, VARIOUS HYDROCARBONS, OXIDES OF NITROGEN, OXIDES OF SULFUR, OXIDES OF PHOSPHORUS AND METAL OXIDE(S).
*** SECTION 06 - TOXICOLOGICAL PROPERTIES ***
EFFECTS OF OVEREXPOSURE-ACUTE & CHRONIC: <inhalation>> SHOULD NOT BE HARMFUL. IF HEATED TO HIGH TEMPERATURE MAY PRODUCE THE FOLLOWING: IRRITATION OF UPPER RESPIRATORY TRACT. <skin contact="">> ACUTE EXPOSURE-SHOULD NOT BE HARMFUL. CHRONIC EXPOSURE MAY PRODUCE THE FOLLOWING: IRRITATION. CHRONIC EXPOSURE MAY PRODUCE THE</skin></inhalation>

FOLLOWING: OIL ACNE. <---EYE CONTACT--->> MAY PRODUCE THE FOLLOWING: Page 2 of 4

Global Parts Order Processing Material Safety Data Sheet SELKIRK CHRYSLER (MB) LTD.

March 14, 2013 15:10

IRRITATION, SWELLING OR REDNESS. <<---INGESTION--->> MAY PRODUCE THE FOLLOWING: DIARRHEA. TOXICOLOGICALLY SYNERGISTIC PRODUCTS: PRODUCT LD50: N/AV N/AV N/AV PRODUCT LC50: N/AV N/AV N/AV N/AV *** SECTION 07 - PREVENTIVE MEASURES *** RESPIRATORY PROTECTION: NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. VENTILATION TYPE: NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. PROTECTIVE GLOVES: NEOPRENE GLOVES OR NITRILE RUBBER GLOVES. EYE PROTECTION: SAFETY GLASSES. DO NOT WEAR CONTACT LENSES. OTHER PROTECTIVE EQUIP: NO SPECIAL PROTECTION NEEDED UNDER NORMAL CONDITIONS. STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: SPILLS ARE VERY SLIPPERY. WIPE UP OR SCRAPE UP SMALL SPILL OR RESIDUE. RESIDUE-WASH AREA WITH DETERGENT AND WATER. WASTE DISPOSAL METHODS: DO NOT FLUSH INTO SEWER SYSTEM. DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND FEDERAL REGULATIONS. PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: STORE IN A COOL, DRY PLACE. KEEP FROM HEAT, SPARK OR OPEN FLAMES. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. PRODUCT TENDS TO MAKE SURFACES, SUCH AS FLOORS, SLIPPERY. REACTS WITH OXIDIZERS. REACTS WITH ACIDS. OTHER PRECAUTIONARY MEASURES: DO NOT SMOKE OR EAT WHEN HANDLING THIS SUBSTANCE; WASH THOROUGHLY AFTER USING. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES. *** SECTION 08 - FIRST AID MEASURES *** EMERGENCY FIRST AID PROCEDURES: <----INHALATION--->> REMOVE TO FRESH AIR AT ONCE. <----SKIN CONTACT--->> WIPE OFF WITH A CLOTH. WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. <---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. REMOVE CONTACT LENSES TO ASSURE COMPLETE FLUSHING. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---INGESTION--->> DO NOT INDUCE VOMITING. RINSE MOUTH WITH WATER. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. LARGE QUANTITIES-CONTACT A PHYSICIAN.

*** SECTION 09 - PREPARED BY INFORMATION ***

C6522000 S42090M

Global Parts Order Processing Material Safety Data Sheet SELKIRK CHRYSLER (MB) LTD.

March 14, 2013 15:10

DATA SHEET PREPARED BY:

INDUSTRIAL HYGIENE DEPARTMENT

CHRYSLER

PHONE: 248-512-8260

PREPARED BY:

REVIEWED BY:

STAFF

REVISED BY: